



FLANSCHLAGER 2-LOCH CTL

TYP	Ø WELLE	ABMESSUNGEN							GEWICHT (MB)	MAX. ANZUGSMOMENT	
	mm	A	B	E	G	I	L	S	kg	Ø	Nm
● ○ ● CTL201	12	90,5	66	71,4	18,4	9,5	20	9	0,23	M8	15
● ○ ● CTL202	15	90,5	66	71,4	18,4	9,5	20	9	0,22	M8	15
● ○ ● CTL203	17	90,5	66	71,4	18,4	9,5	20	9	0,21	M8	15
● ○ ● CTL204	20	90,5	66	71,4	18,4	9,5	20	9	0,20	M8	15
● ○ ● CTL205	25	97,0	71	76,2	18,4	10,0	21	9	0,24	M8	15
● ○ ● CTL206	30	112,5	84	90,5	20,5	11,5	23	11	0,36	M10	20
○ ● CTL207	35	126,0	94	101,0	22,5	12,5	25	11	0,52	M10	25
○ ● CTL208	40	150,0	100	119,0	24,0	13,5	27	14	0,67	M12	30

ZUG-RICHTUNG	BRUCHKRAFT (NEWTON)				
	204	205	206	207	208
	9900	10100	14000	14300	14700
	9300	11700	11300	11800	11900
	7200	9400	12000	12600	12800



VARIANTEN / ZUBEHÖR

Material Gehäuse: ✓ Kunststoff PBT (Polybutylenterephthalat)

Lagereinsätze: ✓ MB Edelstahl ✓ B Stahl

Gehäusefarben: ● blau ohne Schmiernippel ○ weiß ● schwarz

Zubehör: ✓ Schutzkappen offen ✓ Schutzkappen geschlossen