



FLANSLAGER 2-LOCH CTL

| TYP | Ø WELLE | ABMESSUNGEN | | | | | | | GEWICHT (MB) | MAX. ANZUGSMOMENT | |
|--------------|---------|-------------|-----|-------|------|------|----|----|--------------|-------------------|----|
| | mm | A | B | E | G | I | L | S | kg | Ø | Nm |
| ● ○ ● CTL201 | 12 | 90,5 | 66 | 71,4 | 18,4 | 9,5 | 20 | 9 | 0,23 | M8 | 15 |
| ● ○ ● CTL202 | 15 | 90,5 | 66 | 71,4 | 18,4 | 9,5 | 20 | 9 | 0,22 | M8 | 15 |
| ● ○ ● CTL203 | 17 | 90,5 | 66 | 71,4 | 18,4 | 9,5 | 20 | 9 | 0,21 | M8 | 15 |
| ● ○ ● CTL204 | 20 | 90,5 | 66 | 71,4 | 18,4 | 9,5 | 20 | 9 | 0,20 | M8 | 15 |
| ● ○ ● CTL205 | 25 | 97,0 | 71 | 76,2 | 18,4 | 10,0 | 21 | 9 | 0,24 | M8 | 15 |
| ● ○ ● CTL206 | 30 | 112,5 | 84 | 90,5 | 20,5 | 11,5 | 23 | 11 | 0,36 | M10 | 20 |
| ○ ● CTL207 | 35 | 126,0 | 94 | 101,0 | 22,5 | 12,5 | 25 | 11 | 0,52 | M10 | 25 |
| ○ ● CTL208 | 40 | 150,0 | 100 | 119,0 | 24,0 | 13,5 | 27 | 14 | 0,67 | M12 | 30 |

| ZUG-RICHTUNG | BRUCHKRAFT (NEWTON) | | | | |
|--------------|---------------------|-------|-------|-------|-------|
| | 204 | 205 | 206 | 207 | 208 |
| | 9900 | 10100 | 14000 | 14300 | 14700 |
| | 9300 | 11700 | 11300 | 11800 | 11900 |
| | 7200 | 9400 | 12000 | 12600 | 12800 |



VARIANTEN / ZUBEHÖR

| | |
|-------------------|----------------------------------------------------|
| Material Gehäuse: | ✓ Kunststoff PBT (Polybutylenterephthalat) |
| Lagereinsätze: | ✓ MB Edelstahl ✓ B Stahl |
| Gehäusefarben: | ● blau ohne Schmiernippel ○ weiß ● schwarz |
| Zubehör: | ✓ Schutzkappen offen ✓ Schutzkappen geschlossen |