



| CODICE - CODE | descrizione description | DIMENSIONI PRINCIPALI - MAIN DIMENSIONS | | | | | | | CARICO STATICO STATIC LOAD NEWTON |
|---------------|----------------------------|---|-----|------|-----|-----|----|-----|---|
| | | A | B | D | CH | F | G | H | |
| 24500/EB | M10X50 | 29 | 50 | Ø 50 | 14 | M10 | 19 | 79 | 4000 |
| 24502/EB | M10X75 | 29 | 75 | Ø 50 | 14 | M10 | 19 | 104 | 4000 |
| 24504/EB | M10X100 | 29 | 100 | Ø 50 | 14 | M10 | 19 | 129 | 4000 |
| 24506/EB | M10X125 | 29 | 125 | Ø 50 | 14 | M10 | 19 | 154 | 4000 |
| 24600/EB | M12X50 | 29 | 50 | Ø 50 | 14 | M12 | 19 | 79 | 4000 |
| 24602/EB | M12X75 | 29 | 75 | Ø 50 | 14 | M12 | 19 | 104 | 4000 |
| 24604/EB | M12X100 | 29 | 100 | Ø 50 | 14 | M12 | 19 | 129 | 4000 |
| 24606/EB | M12X125 | 29 | 125 | Ø 50 | 14 | M12 | 19 | 154 | 4000 |
| 24608/EB | M12X150 | 29 | 150 | Ø 50 | 14 | M12 | 19 | 179 | 4000 |
| 24700/EB | M14X75 | 29 | 75 | Ø 50 | 14 | M14 | 19 | 104 | 4000 |
| 24702/EB | M14X100 | 29 | 100 | Ø 50 | 14 | M14 | 19 | 129 | 4000 |
| 24704/EB | M14X125 | 29 | 125 | Ø 50 | 14 | M14 | 19 | 154 | 4000 |
| 24706/EB | M14X150 | 29 | 150 | Ø 50 | 14 | M14 | 19 | 179 | 4000 |
| 24708/EB | M14X175 | 29 | 175 | Ø 50 | 14 | M14 | 19 | 204 | 4000 |
| 24800/EB | M16X75 | 32 | 75 | Ø 50 | 13* | M16 | 19 | 107 | 4000 |
| 24802/EB | M16X100 | 32 | 100 | Ø 50 | 13* | M16 | 19 | 132 | 4000 |
| 24804/EB | M16X125 | 32 | 125 | Ø 50 | 13* | M16 | 19 | 157 | 4000 |
| 24806/EB | M16X150 | 32 | 150 | Ø 50 | 13* | M16 | 19 | 182 | 4000 |
| 24808/EB | M16X175 | 32 | 175 | Ø 50 | 13* | M16 | 19 | 207 | 4000 |
| 24810/EB | M16X200 | 32 | 200 | Ø 50 | 13* | M16 | 19 | 232 | 4000 |

* 2 flat sides

• Load values above mentioned have to be considered referring to static conditions calculated at the half of the screw length. In conditions of vibrations or in presence of dynamic loads these values should be reduced. For further information consult our technical office. We cannot accept responsibility for mounts that have been tampered or modified